DL ÉQUIPEMENT
built for safety

ISOWARM
QUALITY PROTECTION FOR HOT WORK

Molleton Kevlar Hood

Glassworks - Industrial Maintenance

REF: DLC02/801/XX
(XX = size)

VERSION 10/2026

Hood made of 100% para-aramid kevlar Molleton fabric, felt insulation, Proban cotton lining, hook-and-loop fastening, drawstring, Kevlar thread stitching and without shoulder cape.

Possible options: head circumference according to customer request.

This PPE complies with Regulation (EU) 2016/425 and has been granted EU type-examination certificate no. 2500222.C1 version 02 issued by TTS- Total Testing Services srl, European notified body 2959.
This PPE is verified by the MODULE D audit carried out by Quintin Certifications, European notified body 2927. EU Declaration of Conformity: available for download on our website: www.dl-equipement.fr (enter the product code; the download is available below the product description)



Instructions and precautions for use:
This work hood, made of molleton kevlar fabric with 1 insulating interlayer and a 100% cotton lining treated with Proban, is designed to be worn when approaching areas of significant heat.
Each time the dlc02/801/xx hood is used, check that it is neither torn nor dirty, as tears or soiling may reduce its protective performance. This hood must always be worn fully closed and together with the dlv10/8xx/xx jacket and the dlp10/8xx/xx trousers to ensure identical protection of the body.
For optimum protection, we recommend using the hood with the dlc30/1XX/XX balaclava: triple-layer balaclava (meta-aramid and para-aramid), EN ISO 11612 : 2015 A1 B3 C2.

Protection limits:
The protection is identical over the entire surface of the garment. The hood must always be worn with a coverall offering at least the same performance according to EN ISO 11612.
This hood is not suitable for work areas where there is a risk of molten material splashes; in that case it is essential to use a garment made of aluminised fabric in order to ensure protection suited to the risks.
The flame-retardant treatment of the lining is guaranteed provided the recommended washing instructions are followed. In the event of an accidental splash of a chemical or flammable liquid, the wearer must remove the hood and make sure that the liquids have not come into contact with the skin. The hood must then be cleaned or withdrawn from service.

Packaging & storage:
Item delivered in a shipping carton without other packaging (no specific packaging required). Recommended storage in a dry & clean place, away from light, in order to maintain the level of protection corresponding to the tests carried out.

Care, cleaning:
Domestic washing according to ISO 6330, 5 washing cycles; the washing temperature must not exceed 40°C.
Do not bleach - Do not tumble dry - Iron at 150°C (2 dots) - Do not dry clean
DL Equipement SARL is the only company authorised to repair the dlc02/801/xx hoods, in order to guarantee the use of the materials certified in the conformity file.
If the garment has hook-and-loop fasteners, make sure they are fully closed before washing. Preferably place the garment in a laundry bag. Do not use any cleaning products.

Made in France

Adverse effects & allergies: No cases to our knowledge.

Recycling & disposal: To our knowledge, the materials used in the manufacture of this item present no particular harmfulness; this garment may be disposed of or recycled in accordance with good practice.

EN ISO 13688 : 2013 + A1 :2021
EN ISO 11612 : 2015

EN ISO 11612

A1 B3 C4 F3

A1 - Limited flame spread (surface ignition)
B3 - Convective heat (Level 1 to 3)
C4 - Radiant heat (Level 1 to 4)
F3 - Contact heat (Level 1 to 3)

Date of manufacture: on label (YEAR_MONTH_XXXX.(XXXX=traceability tracking)

Use-by limit: do not exceed 10 years.
/!\ Provided that the instructions for use and storage are followed.

Hoods – Head circumference				
56	58	60	62	64

Click here to learn more about the standards